

وظيفة التنظيف الذاتي
SELF-CLEANING
FUNCTION

مروحة متعددة السرعات
WIDE-ANGLE LOUVERS

التحكم باتجاه دفع الهواء
AIR FLOW DIRECTION
CONTROL



MODEL NO.		AIMAX	GWC24AVEXF-D6NTA1A	GWH24AVEXF-D6NTA1A	GWC30AVEXH-D6NTA1A	GWC36AWFXH-D6NTA1A
Cooling Capacity (T1)	BTU/h		23200	23200	30000	33000
	KW		6.81	6.81	8.8	9.65
Cooling Capacity (T3)	BTU/h		21300	21700	26000	29400
	KW		6.24	6.36	7.6	8.6
Heating Capacity (T1)		BTU/h	-	21500	-	-
Electric Data	Cooling Power Input(T1)	W	1871	1871	2422	2636
	Cooling Current(T1)	A	8.2	8.2	11.0	11.5
	Cooling Power Input(T3)	W	2302	2347	2960	3230
	Cooling Current(T3)	A	10.1	10.1	13.0	14.0
	Heating Power Input	W	-	1680	-	-
	Heating Current	A	-	7.2	-	-
INDOOR	Air Flow Volume (L - H)	CFM	765 - 647	765 - 647	765 - 618	794 - 618
	Dimension (W*H*D)	mm	1110×347×257		1110×347×257	1350×333×253
	Net Weight	Kg	17	17	18	20
	Noise level (L-H)	dB (A)	40-46	40-46	41-46	43-50
SEER		BTU/(w.h)	10.7	10.75	10.5	10.7
Power supply source		V/Ph/Hz	220V-230V/1Ph/60Hz			
OUTDOOR	Dimension (W*H*D)	mm	958×660×402		1000×746×427	
	Net Weight	Kg	45	48.5	57.5	60.5
	Refrigerant	Type	R32			
	Compressor	Type	ROTARY			
Refrigerant pipe	Liquid pipe	Inch	Φ 1/4	Φ1/4	Φ1/4	Φ1/4
	Gas pipe	Inch	Φ 5/8	Φ5/8	Φ5/8	Φ5/8
	Max. Length	m	40	40	40	40
	Max. Height	m	25	25	25	25